



# 3-point static w/barslides



## PART NO.



## SAMPLE PART

**G L A 2 6 2 8 5 4 - C E - 0 1 2**

The 3-point fixed harness belt assembly is used on various seating arrangements. The lift lever configuration is a standard in the general and commercial aviation markets.

The ABISS line is made of stainless steel to prevent rust and corrosion. Custom plating as well as engraving can be performed. The difference between the GK and the GL is the adjuster on the

BUCKLE CODES		
CODE	P/N	DESCRIPTION
A	1A	35° ALUM. LIFT
B	1B	35° S.S. LIFT
E	1E	90° ALUM. LIFT
F	1F	90° S.S. LIFT

ENDFITTINGS		
4A	4B	4C
4D	4E	4G

ENDFITTING CODES					
CODE	P/N	BOLT HOLE	CODE	P/N	BOLT HOLE
A	4A	.375 HOOK	D	4D	.386 HOLE
B	4B	.25 HOLE	E	4E	.406 HOLE
C	4C	.325 HOLE	G	4G	.386 HOLE

- NOTES:
- STANDARD BUCKLE IS ANODIZED ALUMINUM AND STAINLESS STEEL; PLATED METAL FINISHES AVAILABLE.
  - RESTRAINT ASSEMBLIES CONFORM TO FAA TSO C114.
  - IDENTIFICATION LABELS AFFIXED TO EACH PART OF LAP.
  - LAP ASSEMBLY RATED TO 3000 lbs, HARNESS ASSEMBLY RATED TO 2500 lbs.

## Aircraft Belts

2000 Anders Lane

Kemah, TX 77565 USA

Phone 800.847.5651, Fax 281.538.2225

[www.aircraftbelts.com](http://www.aircraftbelts.com)